



**FS-1370DN**

Black & White Printing Solution

**ECONOMICAL. ECOLOGICAL. ECOSYS PRINTERS.**

- Fast output speed of 37 pages per minute
- Crisp black & white prints
- Low Total Cost of Ownership
- Substantially reduce your operation and maintenance costs
- Eco-friendly long life consumables
- Kyocera ultra-reliable technology



www.bdtme.com  
 1-800-924-4229  
 fax: (207) 777-6377  
 info@bdtme.com





# FS-1370DN



FS-1370DN shown with 2 additional paper feeders for an 800 sheet paper capacity



Print your files directly from memory using the convenient USB Host Interface



Replace the long life toner container quickly and easily

### Basic Specifications

Technology and Configuration	Kyocera ECOSYS® Black & White Network Printer
Pages Per Minute	Letter: 37; Legal: 30; A4: 35
Warm-Up Time	20 seconds or less from main power on, 15 seconds or less from sleep mode
First Print Out Time	7.0 seconds or less (EcoFuser off)
Resolution / Bit Depth	Fine 1200 Mode (1,200 x 1,200 dpi), Fast 1200 Mode (1,800 x 600 dpi), 600 x 600 dpi, 300 x 300 dpi
Memory	Standard 128MB, Upgradable to 1152MB via 144 pin DDR2 SDRAM DIMM, Standard CF Card Slot (Type 1)
Duplex Printing	Standard Duplex
Electrical Requirements	120V, 60Hz, 8.0A; 220V, 50/60 Hz, 4.2A
Dimensions / Weight	14.8"W x 15.5"D x 10.5"H / 26.5 lbs
Typical Energy Consumption (TEC)	2.839 KWh/week
Noise (ISO 7777/ ISO 9296) <sup>1</sup>	Printing: 55dB(A), Ready 30dB(A)
Safety Standards	This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard
Maximum Monthly Duty Cycle	50,000 Pages Per Month

### Controller Specifications

PU / MHz	Embedded Power PC 440F5 / 500 MHz
PDL / Emulations	PRESCRIBE, PCL6 (PCL5c, PCLXL), KPDL (PS3)
Direct Print	PDF Direct Print
Fonts	93 scalable fonts for PCL/PostScript, 8 fonts for Windows Vista, 1 Bitmap font
Barcodes	45 barcodes (e.g. EAN8, EAN13, EAN128), PDF-417-1
Supported Client Operating Systems	Certified for Microsoft® Windows 7, Vista® 32/64-bit, Windows® 2000, Windows XP® 32/64-bit, Windows Server 2003 32/64-bit, Windows Server 2008 32/64-bit; Mac OS X v10.3.9, v10.4, v10.5, v10.6; Linux
Supported Network Operating Systems <sup>2</sup>	Microsoft Windows 2000, Server 2003, XP, Windows 7, Vista, 2003 64-bit, XP 64-bit, Vista 64-bit (for Microsoft IPv6 compatible with Windows 2003, XP, and Vista); Novell 5.1 and later; Mac OS X v10.2.8, v10.3, v10.4, v10.5; Linux, UNIX
Printer Management	Command Center Web Interface, PaperTrail, PDF Direct Print, KMnet Viewer, KMnet Admin, KMnet for Accounting, Internet Printing IPP 1.0
Connectivity / Interfaces	Standard 10/100 Base TX, High Speed USB 2.0, USB Host Printing
Network Protocols <sup>2</sup>	IPv6: HTTP, LPD, FTP, IPP, RawPort, ICMPv6, LLTD, SNMP, DHCPv6, SMTP, POP3, DNS, SNMPv1/v2c/v3, WSD IPv4: HTTP, HTTPS, LPD, FTP, IPP, RawPort, ICMP, DHCP, SMTP, POP3, SNMP, DNS, WINS, NetBIOS over TCP/IP, SNMPv1/v2c/v3, Apple Bonjour Compatible, IPPS, LLTD, WSD Etc.: IPX/SPX, NetWare (NDS/Bindery), AppleTalk, NetBEUI
Security	SSL/TLS (HTTPS, IPPS), SNMPv3, AH, ESP 802.1x authentication (EAP-PEAP, EAP-TLS), IPsec
Drivers	KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Mini Driver, Windows® 64 Bit Drivers

### Paper Supply

Standard Paper Sources	250 Sheet Drawer, 50 Sheet MPT
Standard / Maximum Paper Sources	2 / 4 including MPT
Standard Duplex	20 PPM Letter
Std/Max Paper Capacity	300 / 800 Sheets
Standard Drawer Paper Size / Weight	Letter, Legal, A4, A5, Oficio2, A6, B5, B6, Folio, Statement, Executive, Custom (4.13 x 5.83 to 8.5 x 14) / 16 - 28 lb Bond
MPT Paper Size / Weight	Letter, Legal, A4, A5, A6, B5, B6, Custom (2.76 x 5.83 to 8.5 x 14) / 16 lb Bond - 120 lb Index
Input Materials	Bond, Recycled, Labels, Card Stock, Coated, Postcards, Envelopes, Transparency, Labels, Letterhead, Preprinted, Pre-punched, Colored, Custom
Output Capacity	250 Sheets face down

### Optional PF-100 Paper Feeder

Paper Capacity	250 Sheets
Paper Size / Weight	Letter, Legal, A4, A5, Oficio2, A6, B5, B6, Folio, Executive, Custom (5.83 x 8.26 to 8.5 x 14) / 16 - 28 lb Bond
Input Materials	Bond, Recycled, Letterhead, Preprinted, Pre-punched, Colored, Rough, Custom
Dimensions / Weight	14.8"W x 15.4"D x 3.9"H / 7.7 lbs

The FS-1370DN can be configured with up to 2 additional PF-100 Paper Feeders

### Consumables

Black Toner	TK-172 Toner for 7,200 pages <sup>3</sup> (ships with 2,300 pages)
-------------	--

<sup>1</sup> Sound Pressure  
<sup>2</sup> May require software from the NOS vendor or third-party vendor  
<sup>3</sup> In accordance with ISO 19752

Kyocera Mita America's objective is to manufacture superior products with a low Total Cost of Ownership (TCO) and minimize the impact on the environment. Kyocera's ECOSYS printers incorporate a patented long life drum which is separate from the toner container, eliminating the need to replace the drum when toner is depleted – and reducing landfill waste.

ECOSYS printers provide customers with a printing solution that incorporates long life consumables and one of the lowest costs per print. The operating costs of traditional cartridge-based printers can easily exceed many times the original purchase price during the life of the product. Evaluate your printer costs today. Visit our TCO Tracker at [www.kyoceramita.com](http://www.kyoceramita.com) and start saving.



Specifications and design are subject to change without notice. For the latest on connectivity visit [www.kyoceramita.com](http://www.kyoceramita.com). All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA ©2010 Kyocera Mita America, Inc.

IC# 855D400263

