



## Lexmark X654de

An incredibly large touch screen is just the first of many productivity-boosting features in this robust, high output 4-in-1 laser MFP.

### Print Technology

Monochrome Laser

### Function

Color Scanning, Copying, Faxing, Network Scanning, Printing

### Print Speed (Letter, Black)

Up to 55 ppm

### Print Speed (Letter, Black) Duplex

Up to 37 spm

### Time to First Page (Black)

As fast as 9.5 seconds

### Copy Speed (Letter, Black)

Up to 55 cpm

### Time to First Copy (Black)

As fast as 7.5 seconds

### Print Resolution, Black

1200 Image Quality, 1200 x 1200 dpi, 2400 Image Quality, 600 x 600 dpi

### Scanning Resolution

600 X 600 dpi (black)

### Processor

600 MHz

### Memory, Standard

256 MB

### Memory, Maximum

1280 MB

### Hard Disk

Option available

### Expandable Memory Options

Yes

### Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.2

### Citrix MetaFrame

Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0, Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5, Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64

### Linux Operating Systems Supported

Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10, 11, SUSE Linux Enterprise Desktop 10, openSUSE 10.2, 10.3, 11.0, 11.1, Linspire Linux 6.0, Debian GNU/Linux 4.0, Red Flag Linux Desktop 5.0, 6.0, Ubuntu 7.10, Ubuntu 8.04 LTS, SUSE Linux Enterprise Desktop 11, Debian GNU/Linux 5.0, Ubuntu 8.10, 9.04

### Microsoft Windows Operating Systems Supported

2000, XP, Server 2003, XP x64, Server 2003 running Terminal Services, 2000 Server running Terminal Services, Server 2003 x64, Server 2003 x64 running Terminal Services, Vista, Vista x64, Server 2008, Server 2008 x64, Server 2008 running Terminal Services, Server 2008 x64 running Terminal Services, Windows 7

### Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

### UNIX Operating Systems Supported

Sun Solaris SPARC 8, 9, 10, Sun Solaris x86 10, HP-UX 11.11, 11.23, 11.31, IBM AIX 5.2, 5.3, 6.1

### Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

### Paper Handling Standard

Integrated Duplex, 100-Sheet Multipurpose Feeder, 550-Sheet Input Tray, 550-Sheet Output Bin

### Paper Handling Optional

400-Sheet Universally Adjustable Tray with Drawer, 550-Sheet Drawer, 250-Sheet Drawer, Optional furniture required., 2,000-Sheet High Capacity Feeder (Caster Base required)

### Paper Input Capacity, Standard: Up to

650 pages 20 lb or 75 gsm bond

### Paper Input Capacity, Maximum: Up to

3200 pages 20 lb or 75 gsm bond

### Paper Output Capacity, Standard: Up to

550 pages 20 lb or 75 gsm bond

### Paper Output Capacity, Maximum: Up to

550 pages 20 lb or 75 gsm bond

### ADF Paper Input Capacity

Up to 75 pages 20 lb or 75 gsm bond

### Finishing Option

No

### Number of Paper Inputs, Standard

2

### Number of Paper Inputs, Maximum

6

### Media Types Supported

Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Polyester Labels, Transparencies, Vinyl Labels, Refer to the Card Stock & Label Guide

### Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, A6

### Standard Ports

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), USB Port (Type A) compatible with USB 2.0 Specification, Front USB Port Compatible with USB 2.0 Specification (Type A), Ethernet 10/100BaseTX (RJ-45), also works with 1000Base-T

### Optional Network Ports

Lexmark N4050e 802.11g Wireless Print Server (Print Only), External MarkNet™ N7020e Gigabit Ethernet, Internal MarkNet™ N8120 Gigabit Ethernet, Internal MarkNet™ N8130 Fiber Fast Ethernet, Internal MarkNet™ N8150 802.11b/g/n Wireless

### Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services), Novell Netware Enterprise Print Services), Enhanced IP (Port 9400), FTP, TFTP, IPP 1.1 (Internet Printing Protocol), ThinPrint .print integration

### Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6, TCP, UDP

### Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

### Printable Area

0.167 inches of the top, bottom, right and left edges (within)

### Printer Languages (Standard)

PCL 5e Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, xHTML, PDF 1.6, Direct Image, Microsoft XPS (XML Paper Specification)

### Reduce / Enlarge Range

25 - 400 %

### Scan Area, Maximum

8.5 x 14 inches

### Modem Speed

33.6 Kbps

### Supplies Yield

25,000\*-page High Yield Print Cartridge, 7,000\*-page Print Cartridge, 36,000\*-page Extra High Yield Print Cartridge  
\*Average standard page yield value declared in accordance with ISO/IEC 19752.

### Cartridge(s) Shipping with Product

18,000\*-page starter Return Program Print Cartridge

### Packaged Size (in. - H x W x D)

40.16 x 28.94 x 27.56 in.

### Size (in. - H x W x D)

29.7 x 21.6 x 24.1 in.

### Size, Trays Extended (in. - H x W x D)

29.7 x 21.6 x 31.1 in.

### Weight (lb.)

100 lb.

### Noise Level, Idle

29 dBA

### Print Noise Level, Operating

56 dBA

### Copy Noise Level, Operating

56 dBA

### Scan Noise Level, Operating

55 dBA



www.bdtme.com

1-800-924-4229

fax: (207) 777-6377

info@bdtme.com