



Lexmark X658dtfe

Compact and easy to use, this laser MFP delivers rapid output speeds, extra high-capacity input and the StapleSmart II™ Finisher.

Print Technology

Monochrome Laser

Function

Color Scanning, Copying, Faxing, Network Scanning, Printing

Print Speed (Letter, Black)

Up to 55 ppm

Print Speed (Letter, Black) Duplex

Up to 37 ppm

Time to First Page (Black)

As fast as 9.5 seconds

Copy Speed (Letter, Black)

Up to 55 cpm

Time to First Copy (Black)

As fast as 7.5 seconds

Print Resolution, Black

1200 Image Quality, 1200 x 1200 dpi, 2400 Image Quality, 600 x 600 dpi

Scanning Resolution

600 X 600 dpi (black)

Processor

600 MHz

Memory, Standard

256 MB

Memory, Maximum

1280 MB

Hard Disk

Included in configuration

Expandable Memory Options

Yes

Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.2

Citrix MetaFrame

Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0, Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5, Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64

Linux Operating Systems Supported

Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10, 11, SUSE Linux Enterprise Desktop 10, openSUSE 10.2, 10.3, 11.0, 11.1, Linspire Linux 6.0, Debian GNU/Linux 4.0, Red Flag Linux Desktop 5.0, 6.0, Ubuntu 7.10, Ubuntu 8.04 LTS, SUSE Linux Enterprise Desktop 11, Debian GNU/Linux 5.0, Ubuntu 8.10, 9.04

Microsoft Windows Operating Systems Supported

2000, XP, Server 2003, XP x64, Server 2003 running Terminal Services, 2000 Server running Terminal Services, Server 2003 x64, Server 2003 x64 running Terminal Services, Vista, Vista x64, Server 2008, Server 2008 x64, Server 2008 running Terminal Services, Server 2008 x64 running Terminal Services, Windows 7

Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

UNIX Operating Systems Supported

Sun Solaris SPARC 8, 9, 10, Sun Solaris x86 10, HP-UX 11.11, 11.23, 11.31, IBM AIX 5.2, 5.3, 6.1

Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

Paper Handling Standard

Integrated Duplex, 100-Sheet Multipurpose Feeder, 550-Sheet Input Tray, 550-Sheet Output Bin, 2 x 550-Sheet Drawers, StapleSmart II Finisher

Paper Handling Optional

550-Sheet Drawer, Envelope Feeder

Paper Input Capacity, Standard: Up to

1750 pages 20 lb or 75 gsm bond

Paper Input Capacity, Maximum: Up to

2300 pages 20 lb or 75 gsm bond

Paper Output Capacity, Standard: Up to

1050 pages 20 lb or 75 gsm bond

Paper Output Capacity, Maximum: Up to

1050 pages 20 lb or 75 gsm bond

ADF Paper Input Capacity

Up to 75 pages 20 lb or 75 gsm bond

Finishing Option

Standard

Number of Paper Inputs, Standard

4

Number of Paper Inputs, Maximum

5

Media Types Supported

Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Polyester Labels, Transparencies, Vinyl Labels, Refer to the Card Stock & Label Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, A6

Standard Ports

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), USB Port (Type A) compatible with USB 2.0 Specification, Front USB Port Compatible with USB 2.0 Specification (Type A), Ethernet 10/100BaseTX (RJ-45), also works with 1000Base-T

Optional Network Ports

Lexmark N4050e 802.11g Wireless Print Server (Print Only), External MarkNet™ N7020e Gigabit Ethernet, Internal MarkNet™ N8120 Gigabit Ethernet, Internal MarkNet™ N8130 Fiber Fast Ethernet, Internal MarkNet™ N8150 802.11b/g/n Wireless

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services), Enhanced IP (Port 9400), FTP, TFTP, IPP 1.1 (Internet Printing Protocol), ThinPrint .print integration

Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6, TCP, UDP

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP,

PEAP, TLS, TTLS, IPsec

Printable Area

0.167 inches of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5e Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, xHTML, PDF 1.6, Direct Image, Microsoft XPS (XML Paper Specification)

Reduce / Enlarge Range

25 - 400 %

Scan Area, Maximum

8.5 x 14 inches

Modem Speed

33.6 Kbps

Supplies Yield

25,000*-page High Yield Print Cartridge, 7,000*-page Print Cartridge, 36,000*-page Extra High Yield Print Cartridge *Average standard page yield value declared in accordance with ISO/IEC 19752.

Cartridge(s) Shipping with Product

18,000*-page starter Return Program Print Cartridge

Packaged Size (in. - H x W x D)

56.89 x 39.76 x 33.07 in.

Size (in. - H x W x D)

49.1 x 21.6 x 23.5 in.

Size, Trays Extended (in. - H x W x D)

49.1 x 21.6 x 31.0 in.

Weight (lb.)

176.5 lb.

Noise Level, Idle

28 dBA

Print Noise Level, Operating

55 dBA

Copy Noise Level, Operating

55 dBA

Scan Noise Level, Operating

55 dBA



www.bdtme.com

1-800-924-4229

fax: (207) 777-6377

info@bdtme.com