

Lexmark XS796 Family product specifications



www.bdtme.com
 1-800-924-4229
 fax: (207) 777-6377
 info@bdtme.com

Lexmark XS796de

Lexmark XS796dte

Speeds	
Black and Color	Copy, Print, Scan up to 50 ppm Letter
Paper Handling	
Paper Capacity	Standard Input: 650; Standard Output: 500 Maximum Input: 2,650 (2,000 + 550 + 100); Maximum Output: 1,000
Media Information	Standard Input: 1,750; Standard Output: 500 Maximum Input: 2,300 (550 + 550 + 550 + 550 + 100); Maximum Output: 1,000 Types: Card Stock, Dual Web Labels, Envelopes, Glossy Paper, Integrated Labels, Paper Labels, Plain Paper, Polyester Labels, Transparencies, Vinyl Labels, UV-Resistant Outdoor Media, Banner Media Size: Letter, Legal, Statement, Universal, Folio, Executive, A4, A5, JIS-B5, Envelopes (7-3/4, 9, 10, DL, B5, C5)
ADF Capacity	Up to 75 Sheets
Copy	Touch Screen: 10.2-inch Color, Customizable Memory (Min/Max): 1024 MB/2048 MB Copy Resolution: 600 x 600 dpi
Print	
	Time to First Page: As Fast as 8 Seconds (Black); As Fast as 8.5 Seconds (Color) Resolution: 1200 x 1200 dpi; 4800 Color Quality Processor: 1.2 GHz/Hard Drive: 160+GB Connectivity (Standard): USB 2.0 Specification Hi-Speed Certified (Type B), Front USB 2.0 Specification Hi-Speed Certified Port (Type A), Rear USB 2.0 Specification Hi-Speed Certified Port (Type A), Ethernet 10/100/1000 BaseTX (RJ-45) Connectivity (Optional): Parallel, Serial, Wireless
Scan	
	Scan Features: Resolution: 600 x 600 dpi; ADF Scan: DADF (Single Pass Duplex) Scan Destinations: USB Thumbdrive, E-mail, FTP, IDSS, Network or USB Connected Computer, Windows Network Folder File Formats: TIFF, JPG, PDF, XPS, Secure PDF
Fax	
	Resolution: 600 x 600 dpi Fax Features: Color Fax, Group Fax, Manual Fax, Fax from PC, Up to 512-Character Shortcuts, Fax Preservation, LDAP Look-up, Caller ID, Speed Dials, Block Junk Faxes, Broadcast, Fax Shortcuts, Fax Forwarding
Security	
	User authentication and authorization controls including LDAP; Card reader option to add an extra layer of security; Hard disk encryption protects sensitive data on the disk drive; Automatic scheduled or manual disk wiping; IPsec, SNMPv3 and 802.1x network security supported; Security-audit logging to help track and identify security risks
Supplies Yield	
	Ships with 12,000*-Page (CMYK) Print Cartridges; Aftermarket 18,000*-Page (CMY) Extra High Yield Print Cartridges; 20,000*-page Black High Yield Print Cartridge *Based on approximately 5% print coverage per color. Yields may vary based on actual customer usage.
Recommended Monthly Volume	
	Up to 15,000 Pages/Month
	Contact your dealer about workflow solutions.

Recommended Monthly Page Volume

-Recommended Monthly Page Volume- is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

Trademarks

Lexmark and Lexmark with the diamond design are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. All other trademarks are the property of their respective owners. PCL is a registered trademark of Hewlett-Packard Company. AppleTalk, Mac and Macintosh are trademarks of Apple Computer, Inc., registered in the United States and other countries. MarkNet and MarkVision are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. ENERGY STAR® is a U.S. registered mark. Microsoft, Windows, the Windows logo, Windows Vista, and the Windows Vista logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries. Information in this document is subject to change without notice.

