

MimioCapture



DESCRIPTION

When added to the MimioTeach™ system, the MimioCapture™ tracking system captures and saves whiteboard notations in real time. Whiteboard notes and drawings can be captured in their original marker color and instantly converted to the desired file format. Handwriting can be converted into font-based text. Features include dynamic switching between MimioCapture mode and MimioTeach interactive mode. Also included is a magnetic recharging tray that's durable and easy to mount. MimioStudio™ software in Digital Ink recording mode captures notes, diagrams, charts and illustrations drawn on the whiteboard in an object-based vector format (*.ink) that permits editing and reordering of pages and objects within pages.

PACKAGE CONTENTS

MimioCapture recharging tray, 4 marker pen holders with rechargeable batteries, 4 dry erase Expo™ markers (red, green, blue, black), eraser with rechargeable Lithium-Ion battery, and connector bar (connection to MimioTeach bar).

SPECIFICATIONS

Whiteboard Active Area (per device)

1.5 m x 2.7 m (5 ft x 9 ft)—landscape or portrait orientation.

Positioning for MimioCapture Tray

For MimioCapture operation, the tray should be mounted at the bottom left side of the whiteboard, directly under the MimioTeach bar, and attached to the MimioTeach system by the connector bar.

Recharging Tray Dimensions

54.7 mm H x 902 mm W x 63.7 mm D (2.2 in. H x 35.5 in. W x 2.5 in. D).

Weight

Tray: 0.58 kg (1.3 lb).

Tray, 4 pens, eraser, connector cable: 1.12 kg (2.5 lb).

Controls & Indicators on the Tray

MimioCapture tray serves as a charging station for the batteries inside the pens and eraser.

3 push-button functions on MimioCapture tray: New Page / Copy Page / Print Page.

Marker Pens

Capture Pens use Sanford Expo type dry erase markers.

Pens: 171 mm x 32.2 mm x 32.2 mm (6.7 in. x 1.3 in. x 1.3 in.).

Lithium-Ion battery recharges while pen is docked in the tray.

Eraser

76.11 mm x 76.11 mm x 84.3 mm (3 in. x 3 in. x 3.3 in.).

71 mm (2.8 in.) eraser surface.

Lithium-Ion battery recharges while eraser is docked in the tray.

Power Consumption

5V - 100mA DC via micro-USB

Automatic Mode Switching

Capture mode can be initiated from a MimioTeach system in interactive mode by touching a marker pen to the board, or can be initiated via MimioStudio software.



MimioCapture

SPECIFICATIONS

Certification & Compliance

Safety: UL/CSA/EN/IEC 60950-1 (CE & TUV NRTL) C-Tick, NOM, KCC, GOST, ANATEL, SII, UrkSEPRO, NRCS, VoC, CQC.
EMC: FCC, IC, CE, C-Tick, GOST, KCC, ANATEL, SII.
Environmental: RoHS, WEEE, REACH compliant.

Product Warranty

2 years on all hardware components, extended at no charge to 5 years total with product registration (online or by mail).

Other Available Accessories

Metallic mounting brackets with removable adhesive strips for non-metallic surfaces.
Replacement parts: kit for eraser felt pads, 4 color pens, battery for eraser. North American or International AC adapters.
